

The 1 Touch (Digital with Electronic Temperature Sensor) Family

Specification	Model 930i	Model 920i	Model 910i
Electrical Loading	2.2 kW to 5.2 kW 220 V a.c - 240 V a.c	2.2 kW to 5.2 kW 220 V a.c - 240 V a.c	2.2 kW to 5.2 kW 220 V a.c - 240 V a.c
Built-in Safety Device	EELS 10 mA Sensitivity with Surge Protector	EELS 10 mA Sensitivity with Surge Protector	—
	Heater On / Off Switch	Heater On / Off Switch	Heater On / Off Switch
	Safety Thermal Cut-Out	Safety Thermal Cut-Out	Safety Thermal Cut-Out
	Flow Sensor Switch	Flow Sensor Switch	Flow Sensor Switch
Min. Water Pressure	10 kPa / 1.45 psi / 0.1 bar	10 kPa / 1.45 psi / 0.1 bar	10 kPa / 1.45 psi / 0.1 bar
Max. Water Pressure	380 kPa / 55 psi / 3.8 bar	380 kPa / 55 psi / 3.8 bar	380 kPa / 55 psi / 3.8 bar
Min. Water Flow	2 Litres per Minute	2 Litres per Minute	2 Litres per Minute
Max. Water Flow	8 Litres per Minute	8 Litres per Minute	8 Litres per Minute
Built-in Booster Pump	Pump Motor with Double Ball Bearing	—	—
Water Temp. Control	Electronic Temp. Sensor 33°C to 45°C	Electronic Temp. Sensor 33°C to 45°C	Electronic Temp. Sensor 33°C to 45°C
Water Connection	15 mm Dia. (1/2" BSP) Single Point System	15 mm Dia. (1/2" BSP) Single Point System	15 mm Dia. (1/2" BSP) Single Point System
Dimensions	240 x 360 x 110 mm	240 x 360 x 110 mm	240 x 360 x 110 mm
Weight	4.3 kg	3.3 kg	3.0 kg

The 1 Touch (Analog with Electronic Power Control) Family

Specification	Model 830i	Model 820i	Model 810i
Electrical Loading	2.2 kW to 5.2 kW 220 V a.c - 240 V a.c	2.2 kW to 5.2 kW 220 V a.c - 240 V a.c	2.2 kW to 5.2 kW 220 V a.c - 240 V a.c
Built-in Safety Device	EELS 10 mA Sensitivity with Surge Protector	EELS 10 mA Sensitivity with Surge Protector	—
	Heater On / Off Switch	Heater On / Off Switch	Heater On / Off Switch
	Safety Thermostat	Safety Thermostat	Safety Thermostat
	Flow Sensor Switch	Flow Sensor Switch	Flow Sensor Switch
Min. Water Pressure	10 kPa / 1.45 psi / 0.1 bar	10 kPa / 1.45 psi / 0.1 bar	10 kPa / 1.45 psi / 0.1 bar
Max. Water Pressure	380 kPa / 55 psi / 3.8 bar	380 kPa / 55 psi / 3.8 bar	380 kPa / 55 psi / 3.8 bar
Min. Water Flow	2 Litres per Minute	2 Litres per Minute	2 Litres per Minute
Max. Water Flow	8 Litres per Minute	8 Litres per Minute	8 Litres per Minute
Built-in Booster Pump	Pump Motor with Double Ball Bearing	—	—
Water Temp. Control	Stepless Electronic Power Control	Stepless Electronic Power Control	Stepless Electronic Power Control
Water Connection	15 mm Dia. (1/2" BSP) Single Point System	15 mm Dia. (1/2" BSP) Single Point System	15 mm Dia. (1/2" BSP) Single Point System
Dimensions	240 x 360 x 110 mm	240 x 360 x 110 mm	240 x 360 x 110 mm
Weight	4.3 kg	3.3 kg	3.0 kg



**Built-in
Booster Pump**



**Low
Noise Level**



**Memory
Logic**



**Water
Saving**



FCF Valve



**Electronic Earth
Leakage Sensor**



**Surge
Protector**



**One Push
Feature**



**Maintenance
Assured**



**5 Massage
Spray Mode**